

Estap presents: **EcoLine and EcoLine**

New EcoLine wall mounted cabinet range will make your job much easier with its smart design, advanced features and ease of use.



GENERAL CHARACTERISTICS

- → 4 mm thickness of glass, full-length smoked, shatterproof, tempered, secure
- → Aesthetic design
- → Full glass door
- → 450 mm and 600 mm depth. Double sectioned option (+160 mm) is available for the depth of 450 mm cabinet
- → Special structure allowing the adjustment of 19" device uprights throughout the depth
- → User-friendly, new unified accessories that save space and time
- → Multiple cable entries: Top, bottom and rear
- → Flatpack delivery option which takes less space in storage and transportation*
- → Depending on the different customer needs there are two options available; cabinet with fixed side panels (ECOLINE) and with openable side panels (ECOLINE*)



^{*} Only for Ecoline⁺. Compared with the assembled product, the flatpack product occupies 50% less space.



Advantages of Ecoline and Ecoline[†]

The EcoLine range is ready to carry all the load of your network infrastructure with up to 65 kg of capacity.

EcoLine

- → 65 kg. Load carrying capacity (for wall mounted installation)
- \rightarrow Front door can be opened up to 125°
- → 4U, 7U, 9U, 12U, 16U, 20U height options
- → U marking device installation uprights
- → Nut and washer connection for earthing

EcoLine⁺

- → 65 kg. Load carrying capacity (for wall mounted installation)
- → Front door can be opened up to 125°
- → 4U, 7U, 9U, 12U, 16U, 20U height options
- → U marking device installation uprights
- → Easy openable side panels
- → Nut and washer connection for earthing

Shelves

2-points fixed shelf

4-points fixed and sliding shelves



4-points shelves are only suitable for 600 mm depth cabinets.

Advanced ventilation system

EcoLine and EcoLine plus are equipped with many features for more effective ventilation. Your devices are now more efficient and safe with the circulation system providing optimum air circulation inside the cabinet.





nut and washer!



- dimension of 300 mm x 50 mm
- → Optional brushed cable entry to prevent dust, which will keep the optimum air circulation inside the cabinet

018

TECHNICAL CHARACTERISTICS





- → Assembled
- → 4U, 7U, 9U, 12U, 16U, 20U height options
- → 450 mm and 600 mm depth, double sectioned option (+160 mm) is available for the depth of 450 mm cabinet
- → Standard front door: Single opening full glass, 4 mm thickness full-length smoked, shatterproof, tempered, secure
- → Protection level: IP20
- → Load carrying capacity: 65 kg.
- → 19" uprights: solid metal, 1,5 mm of thickness, 3 bending
- → Side panels: Complete metal, 1 mm
- → Rear panel: 1,5 mm of thickness
- → Door opening ability: 125°
- → Lock: Barrel type locking cabinet, single point locking
- → Surface finish: Durable electrostatic powder coating against impact, scratches and dust
- → Corrosion: ISO9227 and ASTM B 117-85
- → Standards: European Union and international standards; ISO, IEC, EN, Gost, ROHS, UL etc.
- → Color: RAL 9005 black and RAL 7035 light grey



EcoLine[†]

- → 4U, 7U, 9U, 12U, 16U, 20U height options
- → 450 mm and 600 mm depth, double sectioned option (+160 mm) is available for the depth of 450 mm cabinet
- → Standard front door: Single opening full glass, 4 mm thickness full-length smoked, shatterproof, tempered, secure
- → Protection level: IP20
- → Load carrying capacity: 65 kg.
- → 19" uprights: solid metal, 1,5 mm of thickness, 3 bending
- → Side panels: Complete metal, 0,8 mm
- → Rear panel: 1,5 mm of thickness
- → Side panels openable
- → Door opening ability: 125°
- → Lock: Barrel type locking cabinet, single point locking (front door and side covers)
- → Surface finish: Durable electrostatic powder coating against impact, scratches and dust
- → Corrosion: ISO9227 and ASTM B 117-85
- → Standards: European Union and international standards; ISO, IEC, EN, Gost, ROHS, UL etc.
- → Color: RAL 9005 black and RAL 7035 light grey





The Ecoline range is available in flatpack packaging, taking up to **50%** less space



Emek Mahallesi, Ordu Caddesi No: 49 34785 Sancaktepe - Istanbul - Turkey +90 444 34 26



ð